

Material Safety Data Sheet

TriCard PegPower
7-4-9 Liquid Fertilizer

Manufacturer Information

Triangle Chemical Company
P.O. Box 4528
206 Lower Elm Street
Macon, GA 31208

Technical Information: (478) 743-1548
Emergency Telephone Number: ??

Emergency Overview:

Harmful if swallowed. Avoid breathing spray mist. May cause irritation of nose, throat and skin. Avoid contact with eyes, skin or clothing. In case of contact with eyes, flush with copious amounts of water. Consult physician if irritation persists.

Potential Health Effects: Eyes

In case of contact with eyes, flush with copious amounts of water. Consult physician if irritation persists..

Potential Health Effects: Skin

Mild irritation may occur with prolonged contact with the product.

Potential Health Effects: Ingestion

If this product is swallowed, CALL PHYSICIAN OR POISON CONTROL CENTER FOR MOST CURRENT INFORMATION. DO NOT INDUCE VOMITING. Rinse mouth with water immediately, if victim is conscious.

Potential Health Effects: Inhalation

Vapors and mists from the product may cause reversible respiratory irritation.

HMIS Ratings: Health: 2 Fire: 1 Reactivity: 0 Pers. Prot.: B

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

Section 3 – Composition/Information on Ingredients

CAS #	Component	Percent
Blend	Ammonium nitrate, ammonium hydroxide, potassium nitrate, potassium hydroxide, diammonium phosphate, phosphoric acid, tripotassium citrate, potassium chloride, urea. Fulvic acid complex	100

Section 4 – First Aid Measures

Contaminated individuals must be taken for medical attention if any adverse reaction occurs. Rescuers should be taken for medical attention, if necessary. Take a copy of the label and MSDS to physician or health professional with victim.

Section 4 – First Aid Measures (cont.)

SKIN EXPOSURE: If the product contaminates the skin, decontaminate the affected area with running water. The minimum recommended flushing time is 15 minutes, especially if adverse skin reactions occur. If necessary, remove exposed or contaminated clothing, taking care not to contaminate eyes.

EYE EXPOSURE: If this product enters the eyes, open the contaminated individual's eyes while under gently running water. Use sufficient force to open eyelids. Have the contaminated individual "roll" eyes. Minimum flushing is for 15 minutes.

INHALATION: If mists or sprays of this product are inhaled, remove the contaminated individual to fresh air. If necessary, use artificial respiration to support vital functions. Remove or cover gross contamination to avoid exposure to rescuers.

INGESTION EXPOSURE: If this product is swallowed, CALL PHYSICIAN OR POISON CONTROL CENTER FOR MOST CURRENT INFORMATION. DO NOT INDUCE VOMITING. Rinse mouth with water immediately, if victim is conscious. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or unable to swallow. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain an open airway and prevent aspiration. If contaminated individual is convulsing, maintain an open airway and obtain immediate medical attention.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Preexisting respiratory problems, dermatitis, and other skin disorders can be aggravated by exposure to this product.

RECOMMENDATIONS TO PHYSICIANS: Treat symptoms and eliminate overexposure.

Section 5 – Fire Fighting Measures

FLASH POINT: Not applicable.

AUTOIGNITION TEMPERATURE: Not applicable.

FLAMMABLE LIMITS (in air by volume, %):

Lower (LEL): Not applicable.

Upper (UEL): Not applicable.

FIRE EXTINGUISHING MATERIALS:

Water Spray: YES Carbon Dioxide: YES

Foam: YES Dry Chemical: YES

Halon: YES Other: Any "ABC" Class.

UNUSUAL FIRE AND EXPLOSION HAZARDS: When involved in a fire and exposed to extremely high temperatures, the components of this product will decompose to produce irritating vapors and toxic gases (e.g., phosphorous oxides, phosphine, carbon oxides, and ammonia).

Explosion Sensitivity to Mechanical Impact: Not applicable.

Explosion Sensitivity to Static Discharge: Not applicable.

SPECIAL FIRE-FIGHTING PROCEDURES: Incipient fire responders should wear eye protection. Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas.

NFPA Ratings: Health: 1 Fire: 0 Reactivity: 0

Section 6 – Accidental Release Measures

RELEASE RESPONSE: In case of a release, clear the affected area and protect people. Uncontrolled releases should be responded to by appropriately trained personnel in proper personal protective equipment, using pre-planned procedures. In terms of small, incidental releases (e.g., 1 gallon from a leaking container), the minimum personal protective equipment should be as follows: gloves, goggles, and appropriate body protection (e.g., boots, Tyvek suit). For large releases (e.g., 55-gallon drum), the minimum personal protective equipment should be Level C: triple-gloves (rubber gloves and nitrile gloves over latex gloves), chemical resistant suit and boots, hardhat, and an Air-Purifying respirator with a high-efficiency particulate filter. In the event of a spill in which excessive amounts of mists are generated or one in which the level of oxygen is below 19.5% or is unknown, the minimum equipment should be Level B: triple-gloves (rubber gloves and nitrile gloves over latex gloves), chemical resistant suit and boots, hard hat, and Self-Contained Breathing Apparatus. If necessary, dike the spill to prevent releases from contaminating environmentally sensitive areas. Absorb spilled liquid with polypads or other suitable absorbent materials. Rinse area thoroughly with water. Decontaminate the area thoroughly. Place all spill residue in an appropriate container and seal. Reuse this product or dispose of in accordance U.S. Federal, State, or local procedures and appropriate Canadian standards (see Section 13, Disposal)

Section 7 - Handling and Storage

WORK AND HYGIENE PRACTICES: As with all chemicals, avoid getting this product ON YOU or IN YOU. Wash thoroughly after handling this product. Do not eat, drink, smoke, or apply cosmetics while handling this product. Avoid breathing vapors or mists generated by this product. Use in a well-ventilated location. Remove contaminated clothing immediately.

STORAGE AND HANDLING PRACTICES -- NON-BULK CONTAINERS: All employees who handle this material should be trained to handle it safely. Open containers and drums slowly on a stable surface. Open drum bunks carefully to relieve any pressure build-up, which may have developed during storage. All containers of this product must be properly labeled. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, sources of intense heat, or where freezing is possible. Store away from incompatible materials (see Section 10, Stability and Reactivity). Material should be stored in secondary containers or in a diked area, as appropriate. Keep container tightly closed when not in use. Inspect all incoming containers before storage to ensure that containers are properly labeled and are not damaged.

STORAGE AND HANDLING PRACTICES -- BULK CONTAINERS: Bulk containers (e.g., 250 gallon "mini-bulk" tanks) holding this product should be loaded and unloaded in strict accordance with container manufacturer's recommendation and all established on-site safety procedures. Appropriate personal protective equipment must be used (see Section 8, Engineering Controls and Personal Protection). All transfer and dilution equipment must be inspected prior to each use. Transfer and dilution operations must be attended at all times. Hoses must be verified to be clean and free of incompatible chemicals prior to connection to the tank. Valves and hoses must be verified to be in the correct positions prior to starting transfer and dilution operations.

PROTECTIVE PRACTICES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT: Follow practices indicated in Section 6 (Accidental Release Measures). Make certain that application equipment is locked and tagged-out safely, if necessary. Collect all rinsates and dispose of in accordance U.S. Federal, State, or local procedures and appropriate Canadian standards (see Section 13, Disposal Considerations).

Section 8 – Exposure Controls – Personal Protection

VENTILATION AND ENGINEERING CONTROLS: Use with adequate ventilation to prevent inhalation of sprays or mists. All operations should be directed at minimizing the generation of aerosols, sprays, or mists. Eyewash stations/safety showers should be near areas where this product is used or sprayed.

RESPIRATORY PROTECTION: None required under normal circumstances of use. If operations generate aerosols, mists, or sprays which cause exposures in excess of the guidelines listed in Section 2 (Composition and Information on Ingredients), respiratory protection may be needed (e.g., air-purifying respirator with a high efficiency particulate filter) and must comply with the U.S. Federal OSHA Standard (29 CFR 1910.134), applicable U.S. State regulations, or the appropriate standards of Canada and its Provinces. Oxygen levels below 19.5% are considered IDLH by OSHA. In such atmospheres, use of a full-facepiece pressure/demand SCBA or a full facepiece, supplied air respirator with auxiliary self-contained air supply is required under OSHA's Respiratory Protection Standard (1910.134-1998).

EYE PROTECTION: Splash goggles or safety glasses. Wear face shield for operations involving more than 5 gallons of this solution in which splashes or sprays can be generated.

HAND PROTECTION: Wear Neoprene gloves for routine industrial use. Use triple gloves for spill response, as stated in Section 6 (Accidental Release Measures) of this MSDS.

BODY PROTECTION: Use body protection appropriate for task (e.g., coveralls, or rubber apron).

*** Section 9 – Physical & Chemical Properties ***

Appearance:	Dark brown	Odor:	Mild
Physical State:	Liquid	pH:	
Vapor Pressure:	Not applicable	Vapor Density:	Not applicable
Boiling Point:	Not established	Melting Point:	Not applicable
Solubility (H₂O):	Soluble	Specific Gravity:	1.37

*** Section 10 – Chemical Stability & Reactivity Information ***

STABILITY: Stable.

DECOMPOSITION PRODUCTS: When exposed to extremely high temperatures, the components of this product will decompose to produce irritating vapors and toxic gases (e.g., phosphorous oxides, phosphine, carbon oxides, and ammonia).

MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE: Strong bases, strong oxidizers, strong reducers, and water-reactive materials.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Exposure to extreme temperatures and incompatible materials.

*** Section 11 – Toxicological Information ***

Acute and Chronic Toxicity

May cause irritation of nose, throat and skin.

Acute Toxicity-LD50/LC50

Not established

Carcinogenicity

No information is available.

Component Carcinogenicity

No information is available.

***** Section 12 – Ecological Information *****

WORK PRACTICES MUST PREVENT UNINTENTIONAL, ENVIRONMENTAL RELEASES.

ENVIRONMENTAL STABILITY:

The components of this solution are relatively stable, but will decompose over time to generate other inorganic compounds.

International Transportation Regulations

This product is not regulated as a hazardous material by the United States (DOT) or Canadian (TDG) transportation regulations.

Section 13 – Disposal Considerations

PREPARING WASTES FOR DISPOSAL: Waste disposal must be in accordance with appropriate U.S. Federal, State, and local regulations or those of Canada and its Provinces. This product, if unaltered by use, may be disposed of by treatment at a permitted facility or as advised by your local hazardous waste regulatory authority.

U.S. EPA WASTE NUMBER: Not applicable.

Section 14 - Transportation Information

THIS MATERIAL IS NOT HAZARDOUS, PER 49 CFR 172.101, U.S. DEPARTMENT OF TRANSPORTATION.

PROPER SHIPPING NAME: Not applicable.

HAZARD CLASS NUMBER and DESCRIPTION: Not applicable.

UN IDENTIFICATION NUMBER: Not applicable.

PACKING GROUP: Not applicable.

DOT LABEL(S) REQUIRED: Not applicable.

NORTH AMERICAN EMERGENCY RESPONSE GUIDE NUMBER - 1996: Not applicable.

MARINE POLLUTANT: No component of this product is listed as a DOT Marine Pollutant (49 CFR 172.101, Appendix B).

Section 15 – Regulatory Information

ADDITIONAL U.S. REGULATIONS:

U.S. SARA REPORTING REQUIREMENTS: The components of this product are not subject to the reporting requirements of Sections 302, 304 and 313 of Title III of the Superfund Amendments and Reauthorization.

ANSI LABELING (Z129.1): CAUTION! MAY CAUSE SKIN, EYE, AND RESPIRATORY SYSTEM IRRITATION. PROLONGED SKIN CONTACT MAY CAUSE ALLERGIC REACTIONS. HARMFUL IF SWALLOWED. FOR AGRICULTURAL USE ONLY. KEEP AWAY FROM CHILDREN. Avoid contact with skin, eyes, and clothing. Avoid prolonged skin contact. Wash thoroughly after handling. Use in well-ventilated area.

Use gloves, safety goggles, and appropriate body protection. **FIRST-AID:** In case of skin or eye contact, flush with copious amounts of water. Recommended flushing time is for 15 minutes. If inhaled, remove to fresh air. If ingested, do not induce vomiting. If adverse reactions occur, get medical attention. **IN CASE OF FIRE:** Use water fog, dry chemical, CO₂ or "alcohol" foam. **IN CASE OF SPILL:** Absorb with an inert material (e.g., polypads), then place in a suitable container. Consult Material Safety Data Sheet.

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text.