WC-12

Water Conditioning Agent

PRINCIPAL FUNCTIONING AGENTS

Ammonium Hydrogen Sulf	fate23.1%
Ammonium Sulfate	26.29
Water	50.7%

Density: 10.8 lbs./gal @ 68° F


Net Contents and Net Weights:

2.5 U.S. GALLONS (9.5 Liters) and 26.9 lbs. (12.2 kg)

KEEP OUT OF REACH OF CHILDREN WARNING • AVISO

HAZARD STATEMENTS

Causes serious eye irritation. Harmful if swallowed, inhaled, or absorbed through skin.



If you do not understand this label, find someone to explain it to you in detail. (Si usted no entiende la etiqueta, busque a alguien para que se la explique a usted en detalle)



IF IN EYES: Hold eye open and rinse slowly and gently with water for 20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for advice.

IF SWALLOWED: Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything to an unconscious person.

IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of soap and water for 15 to 20 minutes. Call a poison control center or doctor for treatment.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

Have the product container or label with you when calling a poison control center or doctor, or going for treatment.

You may also contact INFOTRAC 1-800-535-5053 for emergency medical treatment.

PRECAUTIONARY STATEMENTS: Do not get in eyes, on skin or on clothing. Wash hands, forearms, and other exposed areas thoroughly after handling. Do not eat, drink or smoke when using this product. Wear impervious gloves, protective clothing, and eye protection (goggles/full face shield). Do not breathe vapors, mist, or spray.

ENVIRONMENTAL PRECAUTIONS: Prevent further leakage or spillage if safe to do so. Do not allow to enter drains, sewers, or watercourses.

BEFORE USING THIS PRODUCT, READ ALL PRECAUTIONS, DIRECTIONS FOR USE, CONDITIONS OF SALE - LIMITED WARRANTY AND LIMITATIONS OF LIABILITIES AND REMEDIES.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

STORAGE: Store in a safe place away from pets and keep out of the reach of children. Store away from excessive heat. WC-12 will freeze. Always store WC-12 above 40 degrees F (Do not Freeze). Freezing may cause product separation.

DISPOSAL CONSIDERATIONS: Dispose of in accordance with local/regional/national regulations.

ADDITIONAL INFORMATION

Information regarding the contents in this product is available by calling 478-743-1548.

DIRECTIONS FOR USE

WC-12 is a water conditioning agent. It reduces the pH of the water solution and sequesters many dissolved mineral ions that tend to tie up or reduce the effectiveness of some herbicides.

In addition, WC-12 can be used as a tool to increase the ability to tank mix certain products and keep them in more of a uniform solution.

WC-12 is compatible with many pesticides and fertilizers. Perform a jar test to check compatibility prior to mixing large quantities. Confirm compatibility with auxin herbicides such as 2,4-D before mixing with water or fertilizers due to local mixing uses. Dicamba should be tested for compatibility with WC-12 and to insure mixture does not increase volatility of dicamba herbicide.

Follow herbicide and pesticide label recommendations when using WC-12.

Read and follow all directions on this label prior to use.

Do not mix with AMS.

Perform a jar test to check compatibility with other products prior to mixing.

MIXING INSTRUCTIONS

- 1. Add total volume of water or fertilizer to tank and turn on agitation.
- 2. Add required amount of WC-12.
- 3. Add any other pesticide to the tank.
- 4. Fill tank with balance of water or fertilizer while maintaining agitation.
- 5. Agitate adequately for uniformity of solution before applying.

RECOMMENDED RATES

Always add WC-12 to spray water solution first to condition the water.

Use Rate: 1/4% - 1% v/v based on water hardness

Use the higher rates in water hardness above 500ppm.

IMPORTANT READ BEFORE USING LIMITED WARRANTY AND LIMITATION OF REMEDIES

Seller warrants that product will be labeled as required under state and federal law and that they conform to the label description. Any nonconformance must be reported in writing to Seller within thirty (30) days after purchase as a prerequisite to maintaining any claim against Seller. Buyer agrees to inspect all product purchased immediately upon delivery.

THE SELLER'S LIABILITY ON THIS WARRANTY IS LIMITED IN AMOUNT TO THE PURCHASE PRICE OF THE PRODUCT. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THIS STATEMENT.





Manufactured For: TRIANGLE CHEMICAL COMPANY 117 PRESTON COURT MACON, GA 31210